

# Circuit breaker Masterpact MTZ1 06H2, 630 A, 3P fixed, without Micrologic

LV847113

### Main

Range	MasterPacT	
product name	MasterPact MTZ1	
Device short name	MTZ1 06 H2	
Product or component type	Circuit breaker	
Device application	Power distribution protection	
Poles description	3P	
Control unit	Without control unit	
Product compatibility	control unit MicroLogic 2.0 X control unit MicroLogic 5.0 X control unit MicroLogic 6.0 X control unit MicroLogic 7.0 X control unit MicroLogic 2.0 Xi control unit MicroLogic 5.0 Xi control unit MicroLogic 6.0 Xi control unit MicroLogic 6.0 Xi control unit MicroLogic 7.0 Xi	
[In] rated current	630 A at 40 °C	
Performance type	H2 50 kA 415 V AC	
[Ue] rated operational voltage	690 V AC 50/60 Hz	
Suitability for isolation	Yes conforming to EN/IEC 60947-2	
Selectivity category	Category B	
control type	Push-button	
Mounting mode	Fixed	

## Complementary

[lcu] rated ultimate short-circuit	50 kA at 220/415 V AC 50/60 Hz
breaking capacity	50 kA at 440 V AC 50/60 Hz
	42 kA at 500/525 V AC 50/60 Hz
	42 kA at 660/690 V AC 50/60 Hz
[lcs] rated service breaking	50 kA at 220/415 V AC 50/60 Hz
capacity	50 kA at 440 V AC 50/60 Hz
	42 kA at 500/525 V AC 50/60 Hz
	42 kA at 660/690 V AC 50/60 Hz
[lcw] rated short-time withstand current	42 kA 0.5 s
	42 kA 1 s
	24 kA 3 s
[lcm] rated short-circuit making	105 kA 220/415 V AC at 50/60 Hz
capacity	105 kA 440 V AC at 50/60 Hz
	88 kA 500/525 V AC at 50/60 Hz
	88 kA 660/690 V AC at 50/60 Hz
Integrated instantaneous	8199 kA

Sensor rating	400 A	
	630 A	
[Ui] rated insulation voltage	1000 V AC 50/60 Hz	
[Uimp] rated impulse withstand voltage	12 kV	
Power dissipation in W	30 W	
Maximum breaking time	25 ms	
Maximum closing response time	50 ms	
Mounting support	Rails Base plate	
Upside connection	Front Rear	
Downside connection	Front Rear	
Connection pitch	70 mm	
Mechanical durability	12500 cycles with periodic preventive maintenance	
Electrical durability	3000 cycles 690 V AC 50/60 Hz conforming to EN/IEC 60947-2 6000 cycles 440 V AC 50/60 Hz conforming to EN/IEC 60947-2 AC-23A: 3000 cycles 690 V AC 50/60 Hz conforming to EN/IEC 60947-3 AC-23A: 6000 cycles 440 V AC 50/60 Hz conforming to EN/IEC 60947-3 AC-3: 6000 cycles 440 V AC 50/60 Hz conforming to EN/IEC 60947-3	
Height	301 mm	
Width	276 mm	
Depth	209 mm	
Net weight	14 kg	
Standards	EN/IEC 60947-1 EN/IEC 60947-2 EN/IEC 60947-2 Annex H IEC 61557-12	
Product certifications	CE IECEE CB Scheme	

## **Environment**

IP degree of protection	IP30 conforming to EN 60529	
Pollution degree	3 conforming to IEC 60947-1	
ambient air temperature for operation	-2570 °C	
Ambient air temperature for storage	-4085 °C	
Operating altitude	02000 m without derating 20005000 m with derating	

## **Packing Units**

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	25.0 cm
Package 1 Width	40.0 cm
Package 1 Length	40.0 cm
Package 1 Weight	15.69 kg



Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing "Use Better, Use Longer, Use Again" campaign to extend product lifetimes and recyclability.

#### Environmental Data explained >

How we assess product sustainability >

⊘ Environmental footprint	
Carbon footprint (kg.eq.CO2 per CR, Total Life cycle)	413
Environmental Disclosure	Product Environmental Profile

#### **Use Better**

Recycled metal content at CR level	0
Packaging made with recycled cardboard	Yes
Packaging without single use plastic	Yes
EU RoHS Directive	Compliant with Exemptions
SCIP Number	44ce05ea-25e9-435c-886d-b1162ae4666b
REACh Regulation	REACh Declaration
Halogen content performance	Product contains halogen above thresholds
PVC free	No
Silicon free	No

#### **Use Again**

○ Repack and remanufacture	
Circularity Profile	End of Life Information
Take-back	No
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins